# MONOBEAM 80P

**SIX AXES TIRE RIBBON APPLICATOR**
**Main technical features**
***APPLICATORE GOMMA ESTRUSA A SEI ASSI***
***Principali caratteristiche tecniche***

- pins barrel extruder with diameter 80mm.(3.15"); L/D ratio: 12
- electric motor 45kw 400-460v 50/60Hz
- extruder screw max. speed: 72 rpm
- min. / max. tire diameter: 450 mm (17.75") / 1475 mm (58").
- min. / max. tire width: 150 mm (5.9") / 525 mm (20.67").
- three zones temperature control
- laser sensor for tire profile reading
- reading system of tire diameter (during building) for automatic building parameters progressive adjustment
- overall dimensions (L x H x D):

  4881 (16') x 1475 (4.8') x 2518 mm (8.25'). (including protection barrier);
  4476 (14.6') x 1475 (4.8') x 1620 mm (5.3'). (without protection barrier)
- patented model
- plug and work execution

abm automazione
via Pian delle Capanne 42
19020 Borghetto Vara (SP) Italy
tel: 0187.904141
fax: 0187.8797062
e-mail:abm@abmautomazione.it
www.abmautomazione.it

| Rev. | Compilato Compiled | Controllato Checked | Data Date |
|---|---|---|---|
| | | | |
| | | | |
| | | | |
| 0 | SOMMA E. | BOLLENTINI A. | 04.02.14 |

Documento n.: Document no.: **A3-039- 51**

Foglio: Sheet: 1 / 1